

# NISE 2420

Intel® Atom™ Processor E3845 Quad Core Fanless System



## Main Features

- Onboard Intel® Atom™ processor E3845 Quad core, 1.91GHz
- Dual independent display from DVI-I and HDMI
- 2 x Intel® I210IT GbE LAN ports; support WoL, teaming and PXE
- 2 x RS232 & 2 x RS232/RS422/RS485 with auto flow control
- 4 x USB 2.0 & 1 x USB 3.0
- 2 x mini-PCIe socket for optional mSATA/Wi-Fi/4G LTE/3.5G
- Support -20 to 70 degree Celsius extended operating temperature
- Support 9-30V DC input

## Product Overview

Powered by Intel® Atom™ Bay Trail Quad core processor E3845, 1.91GHz. Driven by the latest Dual Core Intel® Atom™ processor, NISE 2420 can provide excellent computing power and is more power-efficient than the platforms based on the previous generation Intel® Atom™ product family.

NISE 2420 supports up to 8G DDR3L memory and have several options on storage devices like CFast, HDD, SSD or mSATA. The NISE 2420 comes with 1 x HDMI, 1 x DVI-I, 2 x GbE LAN ports, 2x COM port with RS232/422/485 and 5x USB ports including one USB 3.0. NISE 2420 supports 9~30V DC input, and can be operated in an extended operating temperature range from -20 to 70 degrees Celsius. This Fanless system supports two mini-PCIe modules, Which can be an excellent platform for IOT applications (with optional GbE LAN, Wi-Fi, 3.5G/4G LTE module) and factory automation applications with optional fieldbus module expansion versatility makes NISE 2420 a perfect platform for factory automation and M2M intelligent computing applications.

## Specifications

### CPU Support

- Onboard Intel® Atom™ E3845 Quad core, 1.91GHz
- Support Intel® Atom™ E3800 processor family from Single Core E3815, Dual Core E3825/E3826/E3827 and Quad Core E3845 with difference SKUs

### Main Memory

- 2 x DDR3L SO-DIMM socket, support DDR3L 1066/1333 8GB RAM max., un-buffered and non-ECC

### Display Option

- Dual independent display
  - HDMI and DVI-I
  - HDMI and VGA (via DVI-I connector)

### Front I/O Interface

- ATX power on/off switch
- 1 x Power status, 1 x HDD access, 1 x battery low, 4 x programming LEDs, 4 x Tx/Rx LEDs, 2 x LAN LEDs
- 2 x DB9 RS232 for COM3 & COM4
- 1 x External CFast socket
- 1 x SIM card holder
- 1 x USB 3.0 (900mA Max.)
- 1 x Mic-in & 1 x Line-out

- 2 x Antenna holes for optional Wi-Fi/3.5G antenna

### I/O Interface - Rear

- 4 x USB 2.0
- 1 x DVI-I display output
- 1 x HDMI display output
- 1 x Remote power on/off switch
- 2 x Intel® I210IT GbE LAN ports; support WoL, teaming and PXE
- 2 x DB9 for COM1 & COM2, both support RS232/422/485 with auto flow control
  - Jumper-free setting on RS232/422/485
- 1 x 3-pin DC input, support +9 to 30VDC input

### I/O Interface - Internal

- 4 x GPI and 4 GPO (5V, TTL type)


### Storage Device

- 1 x CFast card socket (SATA 2.0)
- 1 x 2.5" HDD space (SATA 2.0)
- 1 x mSATA from mini-PCIe socket if SATA HDD is not installed

### Expansion Slot

- 2 x mini-PCIe socket for optional Wi-Fi/4G LTE/3.5G
- NISE 2420: two PCI Expansion

## Dimension Drawing



- Add-on card length: 176mm max.
- Power consumption: 10W/slot max.

### Power Requirement

- Power input: +9Vdc to +30Vdc
- 1 x Optional 24V, 60W power adapter

### Dimensions

- 195mm (W) x 200mm (D) x 111mm (H) without wall-mount bracket

### Construction

- Aluminum and metal chassis with fanless design

### Environment

- Operating temperature:  
Ambient with air flow: -20°C to 70°C  
(according to IEC60068-2-1, IEC60068-2-2, IEC60068-2-14)
- Storage temperature: -30°C to 85°C
- Relative humidity: 10% to 95% (non-condensing)
- Shock protection:  
HDD: 20G, half sine, 11ms, IEC60068-2-27  
CFast: 50G, half sine, 11ms, IEC60068-2-27
- Vibration protection w/ HDD condition:  
Random: 0.5Grms @ 5~500Hz, IEC60068-2-64  
Sinusoidal: 0.5Grms @ 5~500Hz, IEC60068-2-6
- Vibration protection w/ CFast & SSD condition:  
Random: 2Grms @ 5~500Hz, IEC60068-2-64  
Sinusoidal: 2Grms @ 5~500Hz, IEC60068-2-6

### Certifications

- CE
- FCC Class A

### OS Support Lists

- Windows 8, 32-bit/64-bit
- Windows Embedded Standard 8, 32-bit/64-bit
- Windows 7, 32-bit/64-bit
- Windows Embedded Standard 7, 32-bit/64-bit
- Linux Kernel version 3.8.0

## Ordering Information

- **NISE 2420 (P/N: 10J00242000X0)**  
Onboard Intel® Atom™ processor E3845 Quad core, 1.91GHz with two PCI expansion
- **24V 60W AC/DC power adapter w/o power cord**  
**(P/N: 7400060024X00)**