

PICO313 NEW

Pico-ITX SBC with Intel® Pentium® Processor N4200 & Celeron® Processor N3350, LVDS and LAN

Features

- Intel® Pentium® N4200 and Celeron® N3350
- 1 DDR3L SO-DIMM, up to 8GB
- 1 USB 2.0 port
- 2 PCI Express Mini Card slots



Core System



CPU	Intel® Pentium® N4200 and Celeron® N3350 processor onboard
System Memory	1 x 204-pin DDR3L-1867 SO-DIMM, up to 8GB
Chipset	SoC Integrated
BIOS	AMI
SSD	N/A
Watchdog Timer	65535 levels, 1 ~ 65535 sec.
Expansion Interface	1 x full-size PCI Express Mini Card with mSATA supported 1 x half-size PCI Express Mini Card 1 x PCIe x1, 1 x LPC, 1 x DDI, 4 x USB 3.0, 1 x HD audio and 1 x SMBus (through expansion connector)
Battery Lithium	Lithium 3V/220mAh
Power Input	1 x 4 pin connector +12V DC-in only AT Auto Power On function supported
Power Requirements	Intel® Pentium® N4200 @8GB DDR3L Max. RMS. +12V @ 1.6A Intel® Celeron® N3350 @8GB DDR3L Max. RMS. +12V @ 1.4A
Size	100 x 72 mm
Board Thickness	1.6 mm
Temperature	-20°C ~ +70°C (-4°F ~ +158°F), operation
Relative Humidity	10% ~ 95% relative humidity, non-condensing

I/O

MIO	N/A
SATA	1 x SATA-600
Hardware Monitoring	Detect CPU/system temperature, and voltage
Ethernet	1 port 10/100/1000 Mbps supports Wake-on-LAN, PXE Boot ROM with Intel® i211AT
Audio	N/A
USB	1 x USB 2.0
SMBus/I ² C	Yes, for advanced monitoring/control
Digital I/O	4 channels IN/OUT programmed
TPM	ST ST33TPM12LPC with TPM 1.2 compliant

Display

Chipset	Intel® HD graphics
Memory Size	Share system memory
Display Interface	1 x LVDS; 18/24-bit single/dual channel



▲ Assembly view



▲ Side view

Packing List

Standard

Quick installation guide, User's Manual/Utility CD and accessories

Cable

Part Number	Description	Qty
8593A071000E	AX93A07 LVDS to VGA I/O board	1
59403208000E	SATA cable	1
594P8800600E	SATA power cable	1
5078H313000E	Heatspreader	1
5078H100200E	Heatsink	1
594P8802810E	USB cable	1

Ordering Information

Standard

PICO313LG-N4200 (P/N: E38H313100)	Pico-ITX SBC with Intel® Pentium® processor N4200 (1.1 ~ 2.5 GHz, 2 MB Cache, 6W), LVDS, 1GbE LAN and 1 USB 2.0
PICO313LG-N3350 (P/N: E38H313101)	Pico-ITX SBC with Intel® Celeron® processor N3350 (1.1 ~ 2.4 GHz, 2 MB Cache, 6W), LVDS, 1GbE LAN and 1 USB 2.0