

LYNX-612E

LYNX-612E is a compact, fan-less and cable-less PC adopting low power Intel® Apollo Lake processor. With small dimension, DIN-rail mounting and wide voltage DC input, it can easily fit in industrial environment. Legacy RS-232 and RS-232/422/485 help communicate machines to machines; in the meantime, real-time data collected from manufacturing line will be sent to edge and cloud, which benefit factories to make optimal decisions.

Key Features

- Intel® Celeron® Processor
- Support 2x LAN and 1x M.2 for wireless module
- Extended I/O interface of RS-232/422/485
- Heavy Industry EMC standard
- Customized appearance (Optional)
- Extended temperature (Optional)



General

Processor	Intel® Celeron® N3350, 2 cores, 1.1GHz/2.4 GHz, 6W TDP
Memory	4GB onboard LPDDR4, 2400 MT/s, non-ECC; up to 8GB (Optional)
Storage	32GB onboard eMMC 5.0 flash; up to 256GB (Optional)
Power Input	12-30VDC (+/- 20%)
Operating System	Windows® 10 IoT (64bit) Yocto v2.7
Expansion	1x M.2 Key E 2230 for wireless module
Other	TPM 2.0 onboard

Basic I/O Interface

Power Connector	1x 2-Pin Terminal Block
Ethernet	2x 10/100/1000 GbE (Intel® I210)
USB	2x USB 3.0
Display	1x DP v1.4 4096 x 2160 @ 60Hz

Extended I/O Interface

COM/ Console	1x RS-232 1x RS-232/422/485 (BIOS Configurable)
USB	N/A
Expansion	1x M.2 Key B 2242 for storage 1x full-size Mini-PCle

Certification

CE (EN 55032; EN 55024/ EN 55035)

CE (EN 61000-6-4; EN 61000-6-2)

FCC (Part 15 Subpart Class B)

LVD (EN 62368-1)

ENVIRONMENT & MECHANICAL

Storage Temperature	-40 °C ~ 85 °C
Operating Temperature	0°C ~ 50°C
Permissible Humidity	5-95% RH operating, non-condensing 5-95% RH storage, non-condensing
Vibration	1G with DIN-rail mounting 5G with wall mounting (IEC/EN 60068-2-6)
Shock	15G with DIN-rail mounting 50G with wall mounting (IEC/EN 60068-2-27)
Degree of Protection	IP 30
Dimension	100mm (W) x 53.5mm (H) x 92 mm (D)
Net Weight	0.53 KG
Mounting	DIN-rail / Wall Mount

Optional Accessories

Power Adaptor	2-pin terminal block connector to DC jack cable 60W AC to DC Power Adaptor via DC jack
Video Adaptor	DP to VGA/ DP to DVI-D



Portwell, Inc. (headquarter)
No. 242, Bo'AI St., Shu-Lin Dist.
New Taipei City 238, Taiwan
Tel: +886-2-77318888
Fax: +886-2-77319888
E-mail: info@portwell.com.tw
http://www.portwell.com.tw

American Portwell
(Fremont, CA)
Tel: +1-510-403-3399
Fax: +1-510-403-3184
E-mail: info@portwell.com
http://www.portwell.com

Portwell Latin America
(Brazil)
Tel: +55-41-3121-7200
Tel: +55-41-3121-7201
E-mail: vendas@portwell.com.br
http://www.portwell.com.br

European Portwell
Tel: +31-252-620790
E-mail: info@portwell.eu
http://www.portwell.eu

Portwell Deutschland GmbH
Tel: +49-6103-3008-0
Fax: +49-6103-3008-199
E-mail: info@portwell.de
http://www.portwell.de

Portwell UK Ltd.
Tel: +44-1235-750760
Fax: +44-1235-750761
E-mail: info@portwell.eu
http://www.portwell.eu

Portwell Japan, Inc.
Tel: +81-6-4807-7721
Tel: +81-6-4807-7720
E-mail: info@portwell.co.jp
http://www.portwell.co.jp

Portwell Korea, Inc.
Tel: +82-31-450-3043
Fax: +82-31-450-3044
E-mail: info@portwell.co.kr
http://www.portwell.co.kr

Portwell India
Technology
Tel: +91-80-4078-2700
E-mail: info@portwell.in
http://www.portwell.in

Shanghai Portwell
Tel: +86-21-5771-2565
Fax: +86-21-5772-2985
E-mail: info@portwell.com.cn
http://www.portwell.com.cn