

PPC-S152PF

Arestech

15" IP65 Full Frame Stainless Steel Projected Capacitive Touch Panel PC with Intel® Celeron® J1900 Processor



Features

- 15" 1024 x 768 LCD Panel with Projected Capacitive Touch Display
- Intel® Celeron® J1900 2.0GHz
- Supports Two-finger Touch Control while Wearing Gloves
- Completely Flat Front Panel Design
- Stainless Steel IP65 Waterproof Front Cover
- VESA Mounting

Applications

- CNC Control Panel
- Hospitality and Catering Service
- Food Industry Management System
- Animal Feed Production Facility
- Outdoor Kiosk

→ Packing List

Description
1 x PPC-S152PF
1 x Power Adapter


→ Optional Items

Part No.	Description
AWD-4G003	4G(LTE) EG25-G+ 2 antenna, Full size (for global)
AWD-WF001	Wi-Fi 802.11 bgn (1T1R) + 1 Antenna (Single band), Half-size
AWD-WF003	Wi-Fi 802.11 abgn/ac/BT4.0 (2T2R) Module + 2 Antennas (Dual band), Half-size

→ Ordering Information

Part No.	Description
PPC-S152PF-B6A2	15" 4:3 (1024 x 768), 300nits, Stainless Steel IP65 Full Frame Protection, Fanless Panel PC with Intel® Celeron™ J1900 CPU, Projected Capacitive touch, 2 USB 3.0 2 USB2.0, 2 RS-232, 1 RS-232/422/485, Line out, 2 GbE, 1 VGA, 1 HDMI, DC 9-36V, Phoenix Connector

→ Dimensions



1. Screw Length Limitation: 5mm (Calculated from monitor's back cover)
2. Screw Spec Limitation: M4 size

Cut out : 384.7 * 310mm

→ Specifications

Model		PPC-S152PF-B6A2
Processor System	CPU	Intel® Celeron® Processor J1900
	Frequency	Quad-Core up to 2.0 GHz
	L2 Cache	2 MB
	System Chipset	N/A
	BIOS	UEFI
Memory	Technology	DDR3L 1333 MHz SDRAM
	Max. Capacity	8 GB
	Socket	1 (204-pin SO-DIMM)
Display	Panel Size	15" LCD Panel
	Resolution	1024 x 768 (XGA)
	Viewing Angle	80 x 80 (H) x 60 x 80 (V)
	Brightness	300 (cd/m2)
	Color Support	16.7M
	Contrast Ratio	800:1
	Response Time	8 (msec)
	VGA	Up to 1920 x 1200
	HDMI	HDMI 1.4a up to 1920 x 1200
	Dual Display	LCD + VGA, LCD + HDMI
Touchscreen	Touchscreen Type	Projected Capacitive
	Surface Hardness	7 Mohs
	Durability	-
	Transparency	90% (±3%)
I/O Interface	USB	2 USB 3.0, 2 USB 2.0
	Serial Port	3 COM (2 RS-232, 1 RS-232/422/485)
	Expansion	2 Mini PCIe (1 Full Size and 1 Half-size)
Ethernet	Controller	Dual GbE, 10/100/1000 Mbps (Realtek RTL8111G-CG)
Audio	Chipset	Realtek ALC662 High Definition Audio (HD)
	Connector	Line out
Storage	SATA II	1 Internal 2.5" HDD/SSD
Power	Power Supply Voltage	9-36 V DC input
	Connector Type	2 Pin Terminal Block, Phoenix Connector
	Power Consumption (Typical)	1.53 A @ 12 V (18.4 W)
	Power Consumption (Max.)	1.8 A @ 12 V (21.6 W)
	Battery	Lithium 3 V / 210 mA
Environment	Operating Temperature	-20~60° C (-4~140° F) w/ 2.5" Extended Temperature SSD
	Storage Temperature	-40~85° C (-40~185° F)
	Humidity	5~95% @ 40° C, non-condensing
	Vibration	5-500 Hz, 0.026 G ² /Hz, 2.16 Grms, X, Y, Z, 1 hour per axis
	Certification	CE, FCC Class A
General	Front Panel Waterproof	Front Cover IP65, Full Frame stainless steel
	Dimensions (L x W x H)	386 x 308 x 60 mm (15.20" x 12.13" x 2.36")
	Weight	4.93 kg (10.87 lb)
	Operating System	Windows 7/8.1/10, WES7-E/P, WE8S, Ubuntu 14.04